



# HEAVY-DUTY 15.0 AMP SANDERS AND GRINDERS

**6065-6**  
• 5000 RPM



**6066-6**  
• 6000 RPM



- MILWAUKEE Sanders May Be Converted To Grinders By Using The Proper Wheel Guard For Grinding Operations – (See Accessory Pages)
- Powerful 15.0 Amp 3-1/2 Maximum HP With Long Life Brushes And High Output Fans Provides high performance power for grinding, cutting, and finishing operations.
- Cast Aluminum Gear Housing With Recessed Spindle Lock Accessory change is fast and easy – single wrench operation.
- Optimum Speed Range For Various Accessories Including resin bonded abrasives, wire brushes, resin fiber discs and abrasive flap discs.
- All Ball And Roller Bearing Construction
- Spiral Bevel Gears For optimum motor torque transfer, improved performance and durability. Replaceable armature pinion gear.
- Lock-On Button For Continuous Operation
- 2-Position Side Handle

## ACCESSORIES

### STEEL CARRYING CASE

**48-55-0890** For all 13.0 and 15.0 amp Grinders and Sanders. 6080-20, 6081-20, 6082-20, 6086-20, 6088-20 & 6089-20 sander/grinders will only fit if the wheel & guard are removed.



## SPECIFICATIONS

CATALOG NUMBER	SPEED RPM	DISC DIA.	GUARD TYPE	VOLTS AC-DC	AMPS	MAX. POWER OUTPUT (WATTS)	MAXIMUM HORSEPOWER	SPINDLE THREAD SIZE	LENGTH	NET WGT. LBS.	SHIP. WGT. LBS.
6065-6	5000	7"/9"	—	120	15.0	2610	3-1/2	5/8"-11	17-1/2"	12.0	15.3
6066-6	6000	7"/9"	—	120	15.0	2610	3-1/2	5/8"-11	17-1/2"	12.0	15.3

STANDARD EQUIPMENT: FOR 6065-6 and 6066-6 — Side Handle, Flange and Nylon Washer Only. Order All Accessories Separately.